

Device: Xtium2-CLHS_PX8_1 CameraLink HS Color RGB

Configuration: Select a camera file (Optional)

CameraLink Detecti...

Freeze Snap

Pixel data not available

Parameters ✕

Category	Parameter	Value
Board Basic Timing Advanced Control External Trigger Image Buffer and ROI	Device Scan Type	Linescan
	Sensor Color Type	Color BGR
	Acquisition Line Rate	15000.0
	Measured Line Rate	15000
	Refresh Measured Line Rate	Press...
	Acquisition Frame Rate	Not Enabled
	TDI Mode	TDI BGR
	Align Red Pixels	Off
	Align Red Threshold	50
	Align Red X Shift	5
Attached Camera - Xti... Camera Information Camera Control Digital IO Control Flat Field Image Format File Access Control Transport Layer Acquisition and Transfer C...	Align Red Y Shift	1.0
	Direction Source	Internal
	Internal Scan Direction	Forward
	Analog Gain	1
	Gain Selector	System Gain
	Black Level	0
	Gain	1.0
	Balance White Auto	Press...
	<< Less	

The value entered must be in the range:
Min: 0.000000
Max: 1.000000

Feature Display Name: Align Red X Shift
Description: Align Red X Shift
Feature Name: alignRedXShift
Type: IFloat (SapFeature::TypeDouble)

Buffer ID: 1 << 1 >>

Output Messages